



TECHNICAL DATA SHEET

CEILING PAINT PINK TO WHITE



GENERAL DESCRIPTION:

Fired Earth Ceiling Paint for Ceilings is a quality high hiding acrylic paint, formulated to fade from pink to a brilliant white to achieve a perfect finish every time.

USES:

New or previously painted masonry, plaster, gypsum, concrete, fibre cement and brick surfaces after suitable preparation. All interior surfaces, especially ceilings where resistance to cleaning is not required. May be used as a filler coating under medium quality PVA paints on interior walls over suitably prepared surfaces.

IMPORTANT:

This product may not be tinted. Avoid high condensation areas as this may lead to temporary pink colour which fades away to white on drying.

FEATURES & BENEFITS:

- Lead free
- Water clean-up
- Pink to white, no more missed patches

TECHNICAL INFORMATION	
1. CEILING PAINT	
PHYSICAL FORM	Non-flammable viscous light Pink liquid containing pigments and extenders. May have slight ammonia odour
COLOUR	Light Pink in wet. (White when dry)
FINISH	Smooth and matt
SPREADING RATE	Approximately 6 - 8 m ² / l per application
POLYMER TYPE	Alkali-resistant acrylic copolymer latex
FILLERS	Non-toxic extenders
PIGMENTS	Weather and light resistant types only
DRYING PROPERTIES	Surface or touch-dry: within 1 hour
RECOATING TIME	2 - 4h depending on conditions and film build
FLASH POINT	Not flammable in liquid form
PACKAGING	5L
THINNING	Not recommended, but if required to reduce viscosity add a minimum quantity of WATER. Excessive dilution degrades the quality of the product
CLEANING	Do not allow the product to dry on equipment. Equipment is readily cleaned using (Some detergent may be added to water to facilitate clean up)
APPLICATION METHOD	Supplied ready-for-use. Apply using sheepskin roller or other rollers suitable for waterborne or PVA paints (do not use rollers designed for enamels)

DO NOT PAINT
IF THE TEMPERATURE IS BELOW 10°C OR ABOVE 35°C
IF THE SURFACE IS DAMP (MOISTURE READING ABOVE 15%)
IF IT IS RAINING OR RAIN IS FORECAST
BEFORE 9H00 AND AFTER 16H00 IN THE WINTER

B.DS.056
BW SERIES



**FIRED
EARTH™**

HEALTH & SAFETY

Keep paint away from children. Never smoke, drink or eat while painting. Wear protective overalls, gloves and goggles. If accidental contact with skin should occur, wash immediately with clean water. Harmful if swallowed. Do not induce vomiting. Consult your doctor. Ensure good ventilation during application and drying. Store in a cool, dry place out of the sun.

DISCLAIMER ADVICE

The information given in this Product Information Sheet is based on controlled laboratory tests and many years of experience. It is given in good faith but no guarantee of any performance characteristic is given or implied. Promac Paints cannot be held liable for consequential damage of whatsoever nature that may arise from the use of Promac products. Paint technology is continuously being developed and Promac Paints reserves the right to update product specifications without prior notice. Contact Promac Paints for further details.