



TECHNICAL DATA SHEET

WHISPERS OF WHITE



GENERAL DESCRIPTION:

Whispers of White is a high quality natural low odour washable pure acrylic with a soft subtle sheen finish. Specially formulated from a pure acrylic emulsion, Whispers of White offers excellent flexibility and durability.

USES:

All interior and exterior surfaces after suitable surface preparation and priming.

FEATURES & BENEFITS:

- Low VOC
- Washable
- Flexible
- Alkali resistant

TECHNICAL INFORMATION

1. WHISPERS

PHYSICAL FORM	Non-flammable viscous liquid containing pigments and extenders. Slight ammonia odour
COLOUR	White and standard colours
FINISH	Smooth/subtle sheen finish
SPREADING RATE	Approximately 6 - 8 m ² per litre per application
POLYMER TYPE	Alkali-resistant acrylic copolymer latex
FILLERS	Non-toxic extenders
PIGMENTS	Weather and light resistant types only
DRYING PROPERTIES	Surface or touch-dry: within 1 hour
RECOATING TIME	4 hours depending on conditions during drying
FLASH POINT	Not flammable in liquid form
PACKAGING	5L & 20L
THINNING	Not recommended, but if required to reduce viscosity add a minimum quantity of WATER
CLEANING	Do not allow the product to dry on equipment. Equipment is readily cleaned using water. (Some detergent may be added to water to facilitate clean up)
APPLICATION METHOD	On new Plaster prime with one coat of Plaster primer. Supplied ready-for-use. Apply using a roller suitable for water based ("PVA") paints (do not use rollers designed for enamels). For optimal results apply two coats of Whispers of white paint

DO NOT PAINT

IF THE TEMPERATURE IS BELOW 10°C OR ABOVE 35°C
IF THE SURFACE IS DAMP (MOISTURE READING ABOVE 15%)
IF IT IS RAINING OR RAIN IS FORECAST
BEFORE 9H00 AND AFTER 16H00 IN THE WINTER

HEALTH & SAFETY

Keep paint away from children. Never smoke, drink or eat while painting. Wear protective overalls, gloves and goggles. If accidental contact with skin should occur, wash immediately with clean water. Harmful if swallowed. Do not induce vomiting. Consult your doctor. Ensure good ventilation during application and drying. Store in a cool, dry place out of the sun.

B.DS.009
BW SERIES



**FIRED
EARTH™**

DISCLAIMER ADVICE

The information given in this Product Information Sheet is based on controlled laboratory tests and many years of experience. It is given in good faith but no guarantee of any performance characteristic is given or implied. Promac Paints cannot be held liable for consequential damage of whatsoever nature that may arise from the use of Promac products. Paint technology is continuously being developed and Promac Paints reserves the right to update product specifications without prior notice. Contact Promac Paints for further details.